



Note :

Pin 1 : X1 Left

Pin 2 : Y1 Bottom

Pin 3 : X2 Right

Pin 4 : Y2 Top

Pin Pitch : 1.0 mm

ITO Glass : 1.1 mm

Total Thickness : 1.4 ±0.1 mm

Faceplate Surface : Anti-glare coating

Tolerance: ±0.5 mm

A/A Inside Active

A/A Outside Non-Active

品名	SE-AC15894M	製圖	劉湘明	良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD	單位 : mm	發行日期:	11 - 17 -2005
		確認	陳智誠			變更日期:	

Automobile Touch Panel Specification

SET

Page

2

1. Suitability

This specification suit analog resistance touch panel. which used in LCD module.

2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 78 ~ 84 %

2.3 Operating Temperature : -40°C ~ 80°C

2.4 Thermal shock test : -40°C ~ 110°C

2.5 Storage Temperature : -40°C ~ 85°C

2.6 Operating Voltage : DC5V

2.7 Operating Current : 5mA ~ 25mA

2.8 Isolation Resistance : 20MΩ ↑ @DC25V

2.9 Linearity : ±1.5% ↓

2.10 Operation Pressure : 25 ~ 50g

2.11 Endurance Test strikes : Over 1 million

2.12 Resistance : 150Ω ~ 1200Ω