



Note :

Pin 1 : Bottom (Y2)

Pin 2 : Left (X1)

Pin 3 : Top (Y1)

Pin 4 : Right (X2)

Pin Pitch : 1.0 mm

ITO Glass : 1.1 mm

Total Thickness : 1.4 ±0.2 mm

Faceplate Surface : Anti-glare coating
or Glare coating

A/A Inside Active

A/A Outside Non-Active

品名	SE-AC164101M	製圖	Jason	良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD	單位 : mm	發行日期:	07 - 15 -2005
		確認	Cheng		公差 : ±0.5 mm	變更日期:	

Automobile Touch Panel Specification

SET

Page

2

1. Suitability

This specification suit analog resistance touch panel. which used in LCD module.

2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 78 ~ 84 %

2.3 Operating Temperature : -40°C ~ 80°C

2.4 Thermal shock test : -40°C ~ 110°C

2.5 Storage Temperature : -40°C ~ 85°C

2.6 Operating Voltage : DC5V

2.7 Operating Current : 5mA ~ 25mA

2.8 Isolation Resistance : 20MΩ ↑ @DC25V

2.9 Linearity : ±1.5% ↓

2.10 Operation Pressure : 35 ~ 60g

2.11 Endurance Test strikes : Over 1 million

2.12 Resistance : 150Ω ~ 1200Ω