



Note :

Pin 1 : Bottom

Pin 2 : Right

Pin 3 : Top

Pin 4 : Left

Pin Pitch : 1.0 mm

ITO Glass : 1.1mm

Total Thickness : 1.35 ±0.15 mm

Faceplate Surface : glare coating

V/A : VIEW AREA

A/A : ACTIVE AREA

品名	SE-AC224172	製圖	Jason	良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD	Page : 1/2	發行日期:	10 - 30 -2006
		確認	Cheng			變更日期:	06 - 26 -2007

Touch Panel Specification

SET

Page

2/2

1. Suitability

This specification suit analog resistance touch panel. which used in LCD module.

2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 80 %

2.3 Operating Temperature : -20°C ~ 60°C

2.4 Storage Temperature : -30°C ~ 70°C

2.5 Operating Voltage : DC5V

2.6 Operating Current : 5mA ~ 25mA

2.7 Isolation Resistance : 20MΩ ↑ @DC25V

2.8 Linearity : ±1.5% ↓

2.9 Operation Pressure : 35 ~ 60g

2.10 Resistance : 200Ω ~ 900Ω

2.11 Faceplate Surface : glare coating

2.12 Temperature and Humidity Test : 60°C 90%RH @240 hours