



Note :

Pin Pitch : 1.0 mm

Pin 1 : Left

Pin 2 : Bottom

Pin 3 : Right

Pin 4 : Top

Total Thickness : 2.1 ± 0.2 mm

Faceplate Surface : Anti-glare coating

V/A : VIEW AREA

A/A : ACTIVE AREA

Model No	SE-AC235146	Draw	Jason	良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD	Tolerance ±0.5mm	Date	12-07-2006
		check	Cheng			revise date	

# Touch Panel Specification

SET

Page

2/2

## 1. Suitability

This specification suit analog resistance touch panel. which used in LCD module.

## 2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 78 ~ 84 %

2.3 Operating Temperature : -10°C ~ 60°C

2.4 Storage Temperature : -20°C ~ 70°C

2.5 Operating Voltage : DC5V

2.6 Operating Current : 5mA ~ 25mA

2.7 Isolation Resistance : 20MΩ ↑ @DC25V

2.8 Linearity : ±1.5% ↓

2.9 Operation Pressure : 35 ~ 60g

2.10 Endurance Test strikes : Over 1 million

2.11 Resistance : 200Ω ~ 900Ω

2.12 Faceplate Surface : Anti-glare coating