


DWG No. 2K460702DV1

Unit:mm



Note :

Pin 4 : Right

Pin 3 : Left

Pin 2 : Top

Pin 1 : Bottom

Pin Pitch : 2.54mm

ITO Glass : 1.8 mm

Total Thickness :2.1 ±0.2 mm

Faceplate Surface : glare coating

品名	SE-AM1701-7	製圖	Jason	良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD	單位 : mm 公差 : 一般公差	發行日期:	06 - 07-2004
		確認	Cheng			變更日期:	

Touch Panel Specification

SET

Page

2/2

1. Suitability

This specification suit analog resistance touch panel, which used in LCD module.

2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 80 % ↑

2.3 Operating Temperature : -10°C ~ 60°C

2.4 Storage Temperature : -20°C ~ 70°C

2.5 Operating Voltage : DC5V

2.6 Operating Current : 5mA ~ 25mA

2.7 Isolation Resistance : 20MΩ ↑ @DC25V

2.8 Linearity : ±1.5% ↓

2.9 Operation Pressure : 35 ~ 60g

2.10 Endurance Test strikes : Over 1 million

2.11 Resistance : 200Ω ~ 900Ω

2.12 Faceplate Surface : Anti-glare coating